



Válvula Esférica Acero INOX Bridada - Marca SUN



FEATURES

Material: CF8M (S.S 316) CF8(55 301)

Investment casting body

face to face ANSI B 16.10

Flanged end ANSI B165

Anti-static and fire safe device available

Locking Device available

Suitable medium: water, oil, air and some corrosive liquids

Lever, worm wheel, Pneumatic, etc, operated available

DIMENSIONS LIST (CLASS 150)

SIZE	ON (mm)	D	C	G	T	L	4	W	NM
1/2"	15	89	80.5	35	11.2	108	74	132	4-16
3/4"	20	98	70	43	11.2	117	71.8	132	4-16
1	25	108	79.5	51	12	127	88	170	4-16
1-1/4"	32	117	89	64	12.7	140	92	170	4-16
1-1/2"	40	127	98.5	73	14.3	165	125	233.5	4-16
2"	50	150	120.3	92	16	178	136	233.5	4-19
2-1/2"	65	178	139.5	103	17.5	190	155	233.5	4-19
3"	80	190.5	152.5	127	19.1	203	164	304	4-19
4"	100	229	190.5	157	23.9	229	178	304	8-19
5"	125	251	216	186	23.9	356	263	550	8-22
6"	150	279	241.5	216	25.4	394	293	600	8-22
8"	200	343	298.5	270	28.6	457	345	800	8-22
10"	250	405	362	324	30.3	533.4	GEAR	GEAR	12-26
12"	300	483	432	381	32	609.6	GEAR	GEAR	12-26
14"	350	533	476.5	413	35	686	GEAR	GEAR	12-26

